

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)


(51) International Patent Classification ⁶ : H04L 12/56		A1	(11) International Publication Number: WO 96/36150
			(43) International Publication Date: 14 November 1996 (14.11.96)
(21) International Application Number: PCT/FI96/00256		(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 7 May 1996 (07.05.96)			
(30) Priority Data: 952255 9 May 1995 (09.05.95) FI			
(71) Applicant (for all designated States except US): NOKIA TELECOMMUNICATIONS OY [FI/FI]; Mäkkylän puistotie 1, FIN-02600 Espoo (FI).			
(72) Inventors; and (75) Inventors/Applicants (for US only): KANERVA, Mikko [FI/FI]; Kaarnatie 1 F 58, FIN-00410 Helsinki (FI). KARI, Hannu [FI/FI]; Kullervonkuja 9 B 9, FIN-02880 Veikkola (FI). VAINIKKA, Jari [FI/FI]; Neilikkuja 5 B, FIN-01390 Vantaa (FI). AHOPELTO, Juha-Pekka [FI/FI]; Steniuksentie 23 B 22, FIN-00320 Helsinki (FI).			
(74) Agent: OY KOLSTER AB; Iso Roobertinkatu 23, P.O. Box 148, FIN-00121 Helsinki (FI).			

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: SLIDING-WINDOW DATA FLOW CONTROL USING AN ADJUSTABLE WINDOW SIZE



(57) Abstract

The invention relates to a digital data transmission system with a circuit-switched data connection (V.110) between a transmitting party (A) and a receiving party (B) the nominal data transmission rate of which may vary during the call. A sliding-window data flow control protocol is used on the data connection, in which a number of transmitted data frames to which the transmitting party (A) has not received an acknowledgement from the receiving party (B) is not allowed to exceed the size of the sliding window. In accordance with the invention, a unit (MSC) in the data transmission system that changes the nominal data transmission capacity (data transmission rate) of a non-transparent data connection notifies the change to the transmitting party (A) and to the receiving party (B). This information enables the receiving and transmitting parties to change the size of the sliding window in a controlled manner.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

Sliding-window data flow control using an adjustable window size

Field of the invention

5 The invention relates to sliding-window flow control using an adjustable window size on a non-transparent data connection whose nominal data transmission rate may vary during the connection.

Background of the invention

10 In non-transparent asynchronous data transmission on a circuit-switched connection, data is transmitted from a transmitting party A to a receiving party B in frames or "packets". Besides actual user data, the frames comprise both error-detecting and error-correcting bits to enable
15 the receiving party to detect and possibly correct transmission errors. Each frame is also numbered or the order of the frames is indicated by means of another kind of identifier. The correctness of each received frame is tested at the receiving end. If the frame is found correct,
20 the receiving party acknowledges receipt by transmitting the frame number. If a frame is not found correct (eg due to a transmission error), it will not be further processed (but is "discarded"). A negative acknowledgement (eg a retransmission request) is sent for example in case
25 of discontinuity in frame numbering. Let us assume that a correct frame numbering is, for example 1,2,3,4,5. However, if frame 3 is followed by frame 5, frame 4 is missing and a negative acknowledgement will be sent for frame 4. Once the transmitting end receives a negative
30 acknowledgement or no acknowledgement at all, it retransmits the frame a predetermined number of times. The total number of repetitions is limited, so that endless transmission loops are avoided in a very bad connection.

35 On such a connection user data throughput varies with the quality of the connection. Deterioration in the

quality of the connection results in an increase in the number of incorrect and lost frames, and consequently the number of repetitions.

Moreover, the frames have to be stored (buffered) at the transmitting end until they have been acknowledged so that they are available should retransmission be needed. To limit the amount of necessary buffering, a flow control protocol based on a sliding window may be used in the acknowledgement. In accordance with the flow control protocol the transmitting party A may send a plurality of data frames before requiring acknowledgement from the receiving party. A window represents a sliding sequence of successive frames that have been sent but have not yet been acknowledged (a transmission window). The maximum number of unacknowledged frames equals window size WS. Party B is also prepared to receive WS frames in a reception window, which is a sliding sequence of successive frames that may be acceptably received. The frames that fit into said window but have not arrived in the correct order are gathered into the reception window. Let us assume that frames 1,2,5,6,7 are received. After frames 1 and 2 the window is slid forward, whereas 5, 6 and 7 are stored in the reception window where they wait for the missing frames 3 and 4. Once frames 3 and 4 arrive, the reception window is slid over 3,4,5,6 and 7. When the receiving end acknowledges one or more frames, the reception and transmission windows are slid forward a corresponding number of frames. By means of a sliding window the nominal data transmission capacity of a transmission channel may be better utilized and a higher throughput may be achieved than in a case when the transmitting end A does not send a new frame until it has received an acknowledgement of the previous frame from the receiving end.

An example of data transmission according to the above type is non-transparent asynchronous data transmis-

sion on a circuit-switched connection in the European digital mobile communication system GSM. Herein the sliding-window flow control is Radio Link Protocol RLP in accordance with the GSM specification 04.22. The maximum size of a window is 61 frames, which is also the default value at the beginning of the connection. At the beginning of the connection, by negotiation between the transmitting and receiving parties, the window size may be reduced to a lower value between 1 and 61 to avoid overflows in the transmitting or receiving buffers.

When the nominal data transmission capacity changes, usually leading to a change in the throughput, it is sometimes preferable to change window size WS so that the frame transmission policy is adapted to the new situation. Usually there is no way of knowing in advance when such a change in data transmission capacity will occur. Once the unexpected change has occurred, the transmitting and receiving parties may base their decisions regarding the new situation on eg interpretation of time supervision, requested retransmissions and Receive Not Ready (RNR) messages, as these may be different in the new situation. Such an approach where reaction takes place after a change has occurred, may lead to temporary data flow congestion or to inefficient use of transmission capacity; problems that may not be eliminated until window size WS has been readjusted to comply with the new situation.

The most significant factor limiting transmission capacity in mobile communication systems is the traffic channel at the radio interface. Eg the GSM system cannot at present support user data transmission rates higher than 9.6 kbits/s, which is the maximum user data transmission rate for one full-speed GSM traffic channel.

One solution that enables also higher user data transmission rates in mobile communication systems is disclosed in the applicant's copending Finnish Patent Ap-

plications 942190 and 945817 (unpublished on the priority date of the present application). Herein two or more parallel traffic channels (subchannels) on the radio path are allocated for one high-speed data connection. A high-speed data signal is divided into these parallel subchannels at the transmitting end for transmission over the radio path, and reassembled at the receiving end. This allows the offering of data transmission services where the transmission rate may be even eightfold, depending on the number of allocated traffic channels, compared with the transmission rate of the conventional (single-channel) transmission rate. In the GSM system, for instance, a total user data transmission rate of 19.2 kbits/s is achieved by two parallel subchannels each supporting rate-adapted 9.6 kbits/s as in the existing non-transparent 9.6 kbits/s bearer services of the GSM system.

Consequently, a non-transparent circuit-switched data connection may comprise a plurality of parallel traffic channels at the radio interface, and the number of traffic channels may vary during the connection. The above described problems with adjusting the window size as the nominal data transmission capacity changes, are especially obvious in this kind of multi-channel system where the transmission capacity may even double or increase many-fold in an instant. That is, although the nominal transmission capacity increases, the additional capacity cannot effectively be utilized, at least not without a significant delay, unless the window size is correspondingly increased as soon as possible.

Disclosure of the invention

The object of the invention is to alleviate or eliminate the above problems.

This is achieved with a digital data transmission system comprising a transmitting party, a receiving party, a non-transparent circuit-switched data connection between

the transmitting and receiving parties, control means for changing the data transmission capacity of the data connection, and a sliding-window data flow control protocol where the number of transmitted data frames to which the transmitting party has not received an acknowledgement from the receiving party is not allowed to exceed the size of said sliding window,

A unit in a data transmission system using sliding-window data flow control with an adjustable window size in accordance with the invention, and changing the nominal data transmission capacity (data transmission rate) of a non-transparent data connection, notifies the change to the transmitting party A or the receiving party B or both. By means of this information the receiving and transmitting parties can change the size of the sliding window in a controlled manner. Both parties A and B may adjust the window size independently, in accordance with predetermined rules, or they may start negotiating about the window size. The invention makes it possible to respond to a change in the nominal data transmission capacity simultaneously as the change takes place, and thus the problems, such as temporary congestion of data flow or inefficient utilization of capacity, associated with prior art solutions may be eliminated or alleviated. This is valid for both unidirectional and bidirectional data transmission where both parties can send and receive data.

Brief description of the drawings

The invention will be described below with reference to accompanying drawing in which

Figure 1 illustrates a part of a mobile communication system to which the invention may be applied on a single-channel non-transparent connection.

Figure 2 illustrates a part of a mobile communication system to which the invention may be applied on a multi-channel non-transparent connection.

Figure 3 is a state diagram illustrating a manner of changing the window size when the number of traffic channels on a multi-channel data connection is increased or decreased.

5 Preferred embodiments of the present invention

The present invention may be employed in all digital data transmission systems using sliding-window flow control with an adjustable window size on a non-transparent data connection whose nominal data transmission rate may vary during the connection.

10 The present invention is especially suited for data transmission applications in digital mobile communication systems of the TDMA or CDMA type, such as the European digital mobile communication system GSM, DCS1800
15 (Digital Communication System), a mobile communication system according to the EIA/TIA Interim Standard IS/41.3, etc.

The invention will be described below by using the GSM mobile communication system as an example without being limited to it. The basic structural parts of the GSM
20 system are shown in Figure 1, but in this application there is no need to describe their properties or other sections of the system in greater detail. As to a more detailed description of the GSM system, reference is made
25 to the GSM specifications and the book "The GSM System for Mobile Communications", M. Mouly & M. Pautet, Palaiseau, France, 1992, ISBN: 2-9507190-0-7.

A mobile services switching centre MSC establishes incoming and outgoing calls. The MSC performs similar tasks as an exchange in the public switched telephone
30 network (PSTN). Moreover, the MSC performs functions typical of mobile telephone traffic only, such as subscriber location management, in cooperation with the subscriber registers of the network (not shown). Mobile stations MS
35 communicate with the MSC via base station systems (BSS).

The base station system BSS consists of a base station controller BSC and base transceiver stations BTS.

5 The GSM system is a time division multiple access (TDMA) system where traffic on the radio path is time divided and occurs in successively repeating TDMA frames, each of which consists of a plurality of time slots. A short information packet is sent in each time slot as a radio frequency burst of finite duration and consisting of a group of modulated bits. Time slots are mainly used to
10 convey control channels and traffic channels. Speech or data is transmitted on the traffic channels. Signalling between a base station and a mobile station takes place on the control channels. The channel structures used at the radio interface of the GSM system are described in more detail in the GSM specifications 05.02. In accordance with
15 the specification, one time slot from one of the carrier waves is designated to a mobile station MS as a traffic channel (Single Slot Access) at the beginning of a call. The mobile station MS synchronizes with the time slot to
20 transmit and receive radio frequency bursts.

In the GSM system a data connection is established between a terminal adaptation function TAF 31 of a mobile station MS and an interworking function IWF 41 (usually in connection with the mobile services switching
25 centre MSC) in a fixed network. The data connection is a circuit-switched connection that reserves one (or more) traffic channels from the radio interface for the whole duration of the connection. In the GSM network, the data connection is a V.110 speed-adapted, to V.24 interfaces
30 adaptable digital connection. The herein described V.110 connection is a digital transmission channel originally designed for ISDN technology (Integrated Services Data Network) that adapts to the V.24 interface and offers a chance to transmit also V.24 statuses (control signals).
35 The CCITT recommendation for a V.110 speed-adapted connec-

tion is described in the CCITT Blue Book V.110. The CCITT recommendation for the V.24 interface is presented in the CCITT Blue Book V.24. The terminal adaptation function TAF adapts a data terminal (not shown) connected to a mobile station MS to the V.110 connection, which is established in Figure 1 over a circuit-switched connection using one traffic channel chl. The interworking function IWF adapts the V.110 connection to another V.110 network, such as ISDN or another GSM network, or to another transit network, such as the public switched telephone network PSTN.

Data is transmitted between the terminal adaptation function TAF and the interworking function IWF in frames or "packets" using sliding-window flow control with an adjustable window size. This sliding-window flow control is Radio Link Protocol (RLP) according to the GSM specification 04.22. Data transmission between the interworking function IWF according to the protocol will be described below under the assumption that the interworking function IWF is the transmitting party A and the terminal adaptation function TAF is the receiving party B. It should, however, be noted that data transmission takes place similarly even in the opposite direction, TAF-IWF.

In non-transparent asynchronous data transmission on a circuit-switched connection, data is transmitted from a transmitting party A to a receiving party B in frames or "packets". Besides actual user data, the frames comprise error-detecting bits to enable the receiving party to detect transmission errors. Each frame is also numbered or the order of the frames is indicated by means of another kind of identifier. Party A stores, i.e. buffers, the transmitted frame until receipt from party B of an acknowledgement of successful receipt of the frame. Party B tests the correctness of each received frame. If the frame is found correct, the receiving party acknowledges receipt by transmitting the frame number. If the frame is not

found correct (eg due to a transmission error), it will not be further processed (but is "discarded"). A negative acknowledgement (eg a retransmission request) is sent for example in case of discontinuity in frame numbering. Let us assume, for example, that a correct frame numbering is 1,2,3,4,5. However, if frame 3 is followed by frame 5, frame 4 has been left out and a negative acknowledgement will be sent for frame 4. Once party A receives a negative acknowledgement, or no acknowledgement at all, party A retransmits the frame until an acknowledgement is received or the maximum number of retransmissions is reached. The total number of repetitions is limited so that endless transmission loops are avoided in a very bad connection.

The transmitting party A may transmit a plurality of data frames and buffer them before requiring acknowledgement from the receiving party B. This sliding sequence of successive frames that have been sent but not yet acknowledged, is called a sliding transmission window. The maximum number of unacknowledged frames equals window size WS. In the same way the receiving party B is prepared to receive WS frames in a reception window, which is a sliding sequence of successive frames that can be acceptably received. The frames that fit into said window but have not arrived in the correct order are gathered into the reception window. Let us assume that frames are received in the order 1,2,5,6,7. After frames 1 and 2 the window is slid forward, whereas frames 5, 6 and 7 are stored in the reception window where they wait for the missing frames 3 and 4. Once frames 3 and 4 arrive, the reception window is slid over 3,4,5,6 and 7. When the receiving end acknowledges one or more frames, the reception and transmission windows are slid forward a corresponding number of frames. By means of a sliding window the nominal data transmission capacity of the transmission channel may be better utilized and a better throughput may be achieved

than when the transmitting end A does not send a new frame until it has received an acknowledgement of the previous frame from the receiving end.

5 In accordance with the invention the transmitting party (IWF or TAF) changes the transmission window size WS and the receiving party B (TAF or IWF) changes the reception window size WS when the data transmission capacity on a circuit-switched connection between IWF-TAF changes. In
10 the case of one traffic channel as shown in Figure 1, the change of transfer channel signifies a change in the nominal transmission rate between 2400 bits/s, 4800 bits/s and 9600 bits/s. The procedure that changes the nominal data transmission capacity of the connection is not an essential part of the invention. It may be eg a Channel Mode
15 Modify procedure according to the GSM specification 04.08 (pp. 53-54, 181-182). Typically a call control unit 42 of the mobile services switching centre MSC participates in the changing of the transmission capacity of a data connection, and signals information on the new nominal transmission capacity to a call control unit 32 of the mobile
20 station MS. Even other functional units in the mobile station MS or the mobile services switching centre MSC may bring about or participate in the change of transmission capacity. As to the invention, it not essential which unit or function in the mobile station MS or the mobile services
25 switching centre MSC carries out the change of the nominal transmission capacity or participates therein. As far as the invention is concerned, it is only required that one of these units or functions informs the new nominal data transmission capacity to party A, party B, or
30 both, i.e. to IWF, TAF, or both. It is assumed in the example of Figure 1 that the call control unit 42 informs the change in the nominal data transmission capacity to the interworking function IWF and the call control unit 32 provides the same information to the terminal adaptation
35

function TAF. The information may be the actual nominal data transmission rate, its change, or a simple alarm.

On receiving information on a changed data transmission capacity, parties A and B may adjust their window sizes WS to correspond to the new transmission capacity either independently in accordance with predetermined rules, or they may start negotiating in order to change window size WS. Let it be assumed, for example, that a non-transparent data connection has a nominal transmission capacity of 2400 bits/s, and IWF and TAF receives information on a change in the nominal transmission capacity to the value 4800 bits/s at a certain point of time, which allows the parties A and B to change window size WS accordingly within the limits set by the mobile communication system. Such limits are, eg the buffering capacity of party B, limitations in frame numbering, etc. The window size may be eg 61 frames at data transmission rate 9600 bits/s, 32 frames at data transmission rate 4800 bits/s and 16 frames at data transmission rate 2400 bits/s. These values may be default values that IWF and TAF may change by eg negotiation according to the GSM specification 04.22.

In the example in Figure 1, data transmission on one traffic channel was described, and therefore the highest possible user data transmission rate is limited by the capacity of the traffic channel, eg in the GSM system 9600 bits/s.

The applicant's copending Finnish Patent applications 942190 and 945817 disclose a procedure where a mobile station MS that needs higher-rate data transmission than one traffic channel can offer, is assigned two or more time slots in the same TDMA frame. The maximum user data transmission rate of a multi-channel data connection is the number of parallel traffic channels x the user data transmission rate 9600 bits/s of one traffic channel. In

this way the user rate 19200 bits/s, for instance, may be supplied on two traffic channels as a minimum. This procedure is presented in this application as one example of a manner of embodying high-rate data transmission based on a plurality of parallel traffic channels in a radio system. Regarding the details of this procedure, reference is made to said patent applications. It must, however, be noted that as to the invention, the only essential requirement is that it is possible to establish a multi-channel transmission connection, and the invention is solely directed at the adjustment of the window size when the transfer capacity of such a multi-channel connection is changed by increasing or decreasing the number of traffic channels.

Figure 2 illustrates the architecture of the GSM network that realizes a telefax service of such a group using multiple parallel traffic channels. Figure 2 is identical to Figure 1 except that in Figure 2 a circuit-switched non-transparent connection comprising N parallel traffic channels $ch1-chn$, where $N=1,2,\dots$, exists between the terminal adaptation function TAF and the interworking function IWF. In a mobile station the network termination 31 operates as a divider that divides a high-rate data signal DATA IN received from data terminal equipment into parallel traffic channels $ch1-chn$, and as a combiner that combines low-rate partial signals received from parallel traffic channels $ch1-chn$ into a high-rate data signal DATA OUT. Correspondingly, at the other end of a multi-channel data connection, the interworking function IWF functions as a divider that divides an incoming high-rate data signal DATA IN into parallel traffic channels $ch1-chn$, and as a combiner that combines low-rate partial signals received from parallel traffic channels $ch1-chn$ into a high-rate data signal DATA OUT.

On a multi-channel data connection it is espe-

cially advantageous to be able to change window size WS simultaneously as the nominal transmission capacity changes, in order to utilize the available transmission capacity as efficiently as possible and avoid congestion. Changing the nominal transmission capacity may involve changing the number of radio channels allocated to the connection or changing the nominal transmission rate of one or more traffic channels. Changing the nominal transmission rate of individual traffic channels takes place as in the above case of one traffic channel in Figure 1.

The diagram in Figure 3 illustrates a manner of changing the window size when the number of traffic channels on a multi-channel data connection is increased or decreased. In the following the adjustment of the window size in the interworking function IWF of Figure 2 will be described. The adjustment procedure is similar in the terminal adaptation function TAF.

At the beginning of the connection, when the network adapter is in an initial state 300, init, the initial value of window size WS_0 is given a default value WS_{default} . The default value WS_{default} is dependent on the number of traffic channels, eg $WS_{\text{default}}=61$ when $N=1$.

In state 301, run, IWF performs a data transmission routine using the given window size.

On receiving information on the allocation of a new traffic channel to the radio path for the data connection, IWF moves to state 302, propose new WS. In state 302 IWF proposes a new window size $WS_{\text{proposed}, i+1}$, where the window size is increased by the value WS_{alloc} , which is dependent on both the number of new traffic channels N and the present window size WS_i . IWF then returns to state 301.

On receiving information of the deallocation of a traffic channel used by the data connection on the radio path, IWF moves to state 303, propose new WS. In state 303 IWF proposes a new window size $WS_{\text{proposed}, i+1}$, where the window

size is increased by the value $WS_{dealloc}$, which is dependent on both the number of new traffic channels N and the present window size WS_i . IWF then returns to state 301.

5 Having returned from state 302 or 303 to state 301, IWF either sets $WS_{i+1} = WS_{proposed, i+1}$ as the new window size without negotiating with the terminal adaptation function TAF or starts negotiating with the terminal adaptation function TAF. The negotiation is voluntary or unnecessary when both parties to the connection may be assumed to get
10 information on the change in the number of channels almost simultaneously, in which case they may set the window size independently to the same value.

In case of no negotiation, IWF continues data transmission in state 302 using the new window size
15 $WS_{i+1} = WS_{proposed, i+1}$.

In case negotiation takes place, IWF moves to state 304. In state 304 IWF negotiates with TAF about the window size, eg following the GSM specification 04.22. As a result of the negotiation the window size either remains
20 unchanged, $WS_{i+1} = WS_i$, or a new window size is set in accordance with the proposal, $WS_{i+1} = WS_{proposed, i+1}$ or $WS_{i+1} >$ the proposal of the opposite party. IWF then returns to state 301.

Having returned from state 304 to state 301 IWF
25 continues data transmission using window size WS_{i+1} .

It must be noted that the increase in the window size that IWF chooses in state 302 when a new traffic channel is allocated is not necessarily of the same size as the decrease in the window size that IWF chooses in
30 state 303 when the same traffic channel is deallocated.

In accordance with the diagram shown in Figure 3, several traffic channels may be allocated or deallocated simultaneously. This may take place for instance by performing the change operations of states 302 or 303 several
35 times, one traffic channel at a time, or by performing the

change in window size corresponding to the whole change in the number of channels by one operation of states 302 or 303. In this case the change in window size is not necessarily the sum of changes in individual channels.

5 Traffic channels are typically allocated and de-allocated, i.e. added to or removed from a data connection, by the mobile services switching centre MSC, preferably its call control unit 42, which then signals the information on the allocated traffic channels to the mobile
10 station MS, preferably to its call control 32. From the point of view of the invention, the procedure for allocating traffic channels to a data connection, or the unit or function participating in the allocation, is not essential. As far as the invention is concerned, it is only essential that a unit or function participating in the allocation of traffic channels in a multi-channel connection
15 or in the changing of the nominal data transmission rate, transmits information on the change to the interworking function IWF or to the terminal adaptation function TAF or to both. In the example shown in Figure 2, the call control unit 42 transmits information on the changed nominal transmission capacity to IWF and the call control unit 32 to TAF.
20

25 Even though the invention has been explained with reference to certain embodiments, it will be understood that the description is intended for an example only and changes and modifications may be made to the presented embodiments without departing from the spirit and scope of the invention set forth in the appended claims.

Claims

5 1. Digital data transmission system comprising a transmitting party (A), a receiving party (B), a non-transparent circuit-switched data connection (V.110) between the transmitting and receiving parties, control means (32,42,MSC) for changing the data transmission capacity of the data connection, and a sliding-window data flow control protocol where the number of transmitted data
10 frames to which the transmitting party (A) has not received an acknowledgement from the receiving party (B) is not allowed to exceed the size of said sliding window, characterized in that the transmitting and receiving parties (A,B) are arranged to change the size of
15 said sliding window when one or both of them receive information from said control means (32,42,MSC) on a change in the data transmission capacity of the data connection (V.110).

20 2. System as claimed in claim 1, characterized in that the transmitting party (A) and the receiving party (B) are arranged to change the window size independently, in accordance with predetermined rules, without mutual negotiation.

25 3. System as claimed in claim 1, characterized in that the transmitting party (A) and the receiving party (B) are arranged to change the window size by mutual negotiation.

30 4. System as claimed in claim 1, 2 or 3, characterized in that the data transmission system is a multiple access mobile communication system where a data connection comprises one traffic channel (ch1) on the radio path, and that changing the data transmission capacity of the data connection involves changing the data transmission rate on the traffic channel, and
35 that the change in window size is dependent on the data

transmission rate.

5 5. System as claimed in claim 1, 2 or 3,
characterized in that the data transmission
system is a multiple access mobile communication system
where a data connection comprises one traffic channel or a
plurality of traffic channels (chl-chn) on the radio path,
and that changing the data transmission capacity of the
data connection involves changing the number of traffic
channels allocated to the data connection, and that the
10 change in window size is dependent on the number of said
traffic channels.

 6. System as claimed in any of the claims 1 to 5,
characterized in that the transmitting party
is a terminal adaptation function (TAF) and the receiving
15 party is an interworking function (IWF).

 7. System as claimed in any of the claims 1 to 5,
characterized in that the transmitting party
is an interworking function (IWF) in a mobile communica-
tion network and the receiving party is a terminal adapta-
20 tion function (TAF) in a mobile station.

 8. System as claimed in any of the claims 1 to 5,
characterized in that said control means com-
prise a mobile services switching centre (MSC).




FIG. 1




FIG. 2




FIG. 3

INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 96/00256

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H04L 12/56

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H04L, H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPAT, JAPIO

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4841526 A (JON C. WILSON ET AL), 20 June 1989 (20.06.89), column 8, line 33 - line 48; column 9, line 54 - line 66, claims 1-2,5-7, abstract --	1-4,6-8
X	US 5163046 A (ELLEN L. HAHNE ET AL), 10 November 1992 (10.11.92), column 10, line 21 - line 30; column 11, line 67 - column 12, line 3; column 14, line 21 - line 42, abstract --	1,3,4,6-8
A	US 5193151 A (RAJENDRA K. JAIN), 9 March 1993 (09.03.93), see whole document --	1-8

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search.

8 October 1996

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Date of mailing of the international search report

10-10-1996

Authorized officer

Göran Magnusson
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 96/00256

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5063562 A (TSIPORA P. BARZILAI ET AL), 5 November 1991 (05.11.91), see whole document --	1-8
A	US 4769815 A (MARK G. HINCH ET AL), 6 Sept 1988 (06.09.88), see whole document --	1-8
A	US 4677616 A (ANDREW D. FRANKLIN), 30 June 1987 (30.06.87), see whole document --	1-8
A	US 4736369 A (TSIPORA P. BARZILAI ET AL), 5 April 1988 (05.04.88), see whole document -----	1-8

INTERNATIONAL SEARCH REPORT

International application No.
PCT/FI 96/00256

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A- 4841526	20/06/89	EP-A- 0162478	27/11/85
US-A- 5163046	10/11/92	CA-A, C- 2029054	31/05/91
		CA-A- 2030349	31/05/91
		DE-D- 69025558	00/00/00
		DE-D- 69025713	00/00/00
		EP-A, B- 0430570	05/06/91
		EP-A, B- 0430571	05/06/91
		EP-A- 0687090	13/12/95
		JP-A- 3186042	14/08/91
		JP-A- 3188733	16/08/91
		US-A- 5014265	07/05/91
US-A- 5193151	09/03/93	AU-B- 639017	15/07/93
		AU-A- 6192490	07/03/91
		CA-A- 2023553	01/03/91
		EP-A- 0415843	06/03/91
		JP-A- 3174848	30/07/91
US-A- 5063562	05/11/91	EP-A- 0458033	27/11/91
		JP-A- 7074780	17/03/95
US-A- 4769815	06/09/88	CA-A- 1287151	30/07/91
US-A- 4677616	30/06/87	AU-B- 583946	11/05/89
		AU-A- 6253986	12/03/87
		CA-A- 1252872	18/04/89
		EP-A, B- 0214625	18/03/87
		SE-T3- 0214625	
		JP-B- 6059053	03/08/94
		JP-A- 62062642	19/03/87
US-A- 4736369	05/04/88	DE-D, T- 3787567	11/05/94
		EP-A, B- 0249035	16/12/87
		JP-C- 1778339	28/07/93
		JP-B- 4068662	04/11/92
		JP-A- 62297927	25/12/87

THIS PAGE BLANK (USPTO)